

PRODUCTS SPECIFICATION



MODEL	T04	TS04	CS04	CS08	CD08	CS16	CD16	LS16	LD16	LL16
*DISPLAY SPEED (fps)	25	50	100	100	200	100	200	400	400	400
*RECORD SPEED (fps)	25	50	100	100	200	100	200	100	200	400
VIDEO INPUT	4	4	4	8	8	16	16	16	16	16
AUDIO INPUT	1	2	4	4	8	4	8	4	8	16
SENSOR INPUT	4	4	4	16	16	16	16	16	16	16
ALARM OUTPUT	2	2	4	8	8	8	8	8	8	8
VIDEO RESOLUTION	768X576, 768X288, 384X288									
COMPRESSION TYPE	MPEG-4									
CPU	Cel 1GHz	Cel 1GHz	Cel 1.7GHz	Cel 1.7GHz	Pen 2.4GHz	Cel 1.7GHz	Pen 2.4GHz	Cel 2.0GHz	Pen 2.4GHz	Pen 3.0GHz
MOTHER BOARD	Intel Chipset (845D/PE, 850B/D, 865G/PE)									
MEMORY	256 MB	256 MB	256 MB	256 MB	256 MB	256 MB	256 MB	256 MB	256 MB	512 MB
HDD	120 GB									
VGA	ATI CARD (32 MB)							ATI RADEON 7000 (64 MB)		
O/S	Windows 2000, Windows XP, Linux							Windows 2000, Windows XP		

* speeds for PAL system
 ** system required minimally

For any request or question, please feel free to contact at james@tibetsystem.com