

99100-1 Voice Alert System-6

Voice Alert® System-6 is ideal for residential and small business notification, security, and property protection.



99100



99101

Features:

- Monitors up to 6-Zones
- Adjustable Beam
- Multiple "C" Relays
- All-Weather Construction PIR
- Adjustable PIR Mounting
- Audio Line Output Connection
- Enable/Disable PIR Switch
- Voice Warning for Low Battery

99100: Voice Alert VA-6000S System 6 Wireless Annunciator System

- Records six separate voice messages (6 seconds each)
- Supports an unlimited number of Sensor Transmitters
- Speaker volume control
- Audio Line Output Connection
- Voice message (user initiated): One button for each zone
- Voice message (transmitter initiated): Programmed to desired message (user programmable)
- Individual "C" relays enable other devices to be triggered
- Missed message indicator: Flashing LED
- Missed message playback: Push button
- Receiver type: Super Heterodyne
- Frequency of receiver: 433.92 MHz
- Method of recording: Digital, solid state, user-recordable
- FCC Part 15 Approved
- Receiver Stability: Crystal
- Receiver Sensitivity: 100dBm
- Low Battery LED indicates sensor w/low battery
- Low Battery voice message identifies specific zone
- AC/DC Power Adapter - 6' cord length
- Power Requirement: 117V AC - 60Hz
- Power Input: 9VDC - 1 AMP
- Installation: Wall or tabletop
- Receiver/Speaker Dimensions: 8.50" (W) x 1.75" (H) x 5.75" (D)

99101: Voice Alert VA-6000T System 6 Wireless Sensor/Transmitter

- Monitored range: 40' x 40' feet
- Adjustable (rotating, pivoting) sensor mounting
- Indoor/outdoor all-weather construction
- Adjustable delay timer (0-3 minutes)
- Enable/Disable PIR Switch
- Built-in Contact Closure Connection
- Battery operated - 9V battery included
- Method of intrusion detection: Pyroelectric Infrared Detector (Heat)
- Adjustable Beams:
 - Default: Fan Beam approximately 40' x 40' (mounted 7.5')
 - Options: Vertical Beam, Horizontal Beam
- Frequency of RF transmitter: 433.92 MHz
- Output Power: FCC Part 15 Approved
- Transmission distance: up to 1000' in open space (300 feet through walls)
- Transmitter modulation: OOK (On Off Keying)
- Code programming: User programmable 256 codes
- Power management: Battery saver settings
- Sensor/Transmitter Dimensions: 2.38" (W) x 5.00" (H) x 5.00" (D)
- Operating Temperature: 14°F to 122°F (-10°C to 50°C)

Contact Us:

Security Merchants Pty Ltd • An ASSA ABLOY Group company • www.security-merchants.com

VIC Tel 1300 663 904 • NSW Tel 02 9890 5300 • TAS Tel 03 6272 9262 • QLD Tel 07 3552 5966 • WA Tel 08 9240 7500 • SA Tel 08 8297 5555